
CAVIUS





PRODUCT NAME: CAVIUS HEAT ALARM, 10 YEAR 40MM

PRODUCT NUMBER: 3003

PRODUCT DATA:

DEVICE TYPE: Thermal heat alarm device.

USAGE:

Designed for installation in private homes or garages with risk for smoky, dusty or humid environment, as for example kitchen area, living room with wooden stove burner, garage area.

INSTALLATION POSITION: Wall & ceiling. Set of 2 x screws and 2 x plugs included.

PRODUCT DIMENSIONS: D: 40 mm x H: 40 mm

PRODUCT WEIGHT:

Base alarm weight (excluding screws, plugs and mounting ring): 43 g.

OPERATION AC/DC:

DC

BATTERY TYPE: 3V CR123 Lithium battery, 1600mAh (non-replaceable)

BATTERY LIFE: Minimum 10 year life in normal operating condition. (Based on a weekly testing).

LOW BATTERY INDICATION: A short acoustic "beep" will sound and LED flash every 48 seconds when the voltage is below 2.85V. In this stage it will continue for minimum 30 days, and can drive the alarm for 4 minutes.

NORMAL OPERATION: LED flashes every 48 second for normal operation. SOUND: Audible indicator min. 85 dB @ 3 meter.

SOUND PATTERN: Fire alarm condition is indicated by a series of three successive tones.

VISIBLE INDICATOR: A red LED is used to indicate the following conditions:

- fire alarm condition is indicated by a flash every 0.5 seconds
- normal operation is indicated by a flash every 48
 seconds

PUSH BUTTON:

When the heat detector is in normal operation, pressing the top test button will test all features of the detector: Siren is activated, sensor is tested and LED diode is activated..

DETECTION TIMING: The heat detector is reading every two seconds.

WARRANTY: 10 year

OPERATING TEMPERATURE: +4°C to +38°C

OPERATING HUMIDITY: Up to 90% RH non-condensing **STORAGE TEMPERATURE:** -20°C to +60°C

STORAGE HUMIDITY: Up to 93% RH non-condensing

CONTACT

MANUFACTURER Carrier Fire & Security Danmark A/S



