

CAVIUS


WIRELESS. 
ALARM FAMILY
HEAT
ALARM




DANISH
DESIGN



5 YEAR
BATTERY



100%
TESTED



WIRELESS. 
ALARM FAMILY

HEAT
ALARM

PRODUCT NAME: CAVIUS RF HEAT ALARM, 5 YEAR 65MM

PRODUCT NUMBER: 3103





PRODUCT NAME: CAVIUS RF HEAT ALARM, 5 YEAR 65MM

PRODUCT NUMBER: 3103

PRODUCT DATA:

DEVICE TYPE:

Thermal heat alarm device with wireless interlink.

USAGE:

Designed for installation in private homes or garages with risk for smoky, dusty or humid environment, as for example kitchen area, living room with wooden stove burner, garage area, washing and drying area etc.

This alarm can be connected with other alarms from the CAVIUS Wireless alarm family or function as a stand alone alarm.

INSTALLATION POSITION:

Wall & ceiling. Set of 2 x screws and 2 x plugs included.

PRODUCT DIMENSIONS:

D: 65 mm x H: 39 mm

PRODUCT WEIGHT:

Base alarm weight (excluding screws, plugs and mounting ring): 50 g.

OPERATION AC/DC:

DC

BATTERY TYPE:

3v CR123A lithium battery 1600mAh (replaceable).

BATTERY LIFE:

Minimum 5 year life in normal operating condition. (Based on a weekly testing).

LOW BATTERY INDICATION:

A short acoustic "beep" will sound and LED flash every 48 seconds when the voltage is below 2.85V. In this stage it will continue for minimum 30 days, and can drive the alarm for 4 minutes.

INTERLINK FREQUENCY:

868 MHZ

SIGNALS:

Transmits RF signals to the CAVIUS Wireless Family at alarm.

NORMAL OPERATION:

LED flashes every 48 second for normal operation.

INTERLINK RANGE:

Minimum 100m in open field. Range depends on the building materials and will need to be tested in each individual case.

SOUND:

Audible indicator min. 85 dB @ 3 meter.

SOUND PATTERN:

Heat alarm condition is indicated by a series of three successive tones.

VISIBLE INDICATOR:

A red LED is used to indicate the following conditions:

- alarm condition is indicated by a flash every 0.5 seconds
- normal operation is indicated by a flash every 48 seconds

PUSH BUTTON:

The heat alarm includes a push button switch built into the top of the alarm for easy access. This button has the following functions:

- set up - press the button to start sending out a specific house code to the others alarms

- hush – during an alarm condition this immediately silences the alarm when pressed. When the button is released, the alarm remains silenced for 10 minutes

- test – when not in alarm the sounder can be activated to provide a sensor OK test function. While the button is pressed, the audible and visible indicators are activated if the sensor is OK

DETECTION TIMING:

The heat detector is reading every two seconds.

WARRANTY:

10 year

OPERATING TEMPERATURE:

+4°C to +38°C

OPERATING HUMIDITY:

Up to 90% RH non-condensing

STORAGE TEMPERATURE:

-20°C to +60°C

STORAGE HUMIDITY:

Up to 93% RH non-condensing

CONTACT


www.cavius.com

MANUFACTURER

Carrier Fire & Security Danmark A/S

CAVIUS

WIRELESS ALARM FAMILY



Diameter: 65 mm